

Touchless Wheel Cleaner

Version number: GHS 6.0
Replaces version of: 2024-02-14 (GHS 5)

Revision: 2024-05-17

SECTION 1: Identification

1.1 Product identifier

Trade name

Interchem Touchless Wheel Cleaner

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses

Vehicle wheel cleaner
Professional use
Industrial use

Uses advised against

Do not use for squirting or spraying. Do not use for products which come into direct contact with the skin.

1.3 Details of the distributor

Interchem Limited
9th Avenue South,
Barataria,
Trinidad.

Telephone: 1.868.235.2436,

E-mail: sales@interchem.co.tt

Website: www.interchem.co.tt

SECTION 2: Hazard(s) identification

2.1 Classification of the substance or mixture

Classification acc. to OSHA "Hazard Communication Standard" (29 CFR 1910.1200)

Section	Hazard class	Category	Hazard class and category	Hazard statement
A.1O	acute toxicity (oral)	4	Acute Tox. 4	H302
A.2	skin corrosion/irritation	1B	Skin Corr. 1B	H314
A.3	serious eye damage/eye irritation	1	Eye Dam. 1	H318
A.4S	skin sensitization	1	Skin Sens. 1	H317

For full text of abbreviations: see SECTION 16.

The most important adverse physicochemical, human health and environmental effects

Skin corrosion produces an irreversible damage to the skin; namely, visible necrosis through the epidermis and into the dermis.

2.2 Label elements

Labelling acc. to OSHA "Hazard Communication Standard" (29 CFR 1910.1200)

- Signal word danger

- Pictograms

GHS05, GHS07



Touchless Wheel Cleaner

Version number: GHS 6.0
Replaces version of: 2024-02-14 (GHS 5)

Revision: 2024-05-17

- Hazard statements

H302	Harmful if swallowed.
H314	Causes severe skin burns and eye damage.
H317	May cause an allergic skin reaction.

- Precautionary statements

P260	Do not breathe dust/fume/gas/mist/vapors/spray.
P270	Do not eat, drink or smoke when using this product.
P272	Contaminated work clothing must not be allowed out of the workplace.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P301+P330+P331	If swallowed: Rinse mouth. Do NOT induce vomiting.
P302+P352	If on skin: Wash with plenty of water.
P303+P361+P353	If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
P304+P340	If inhaled: Remove person to fresh air and keep comfortable for breathing.
P305+P351+P338	If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310	Immediately call a poison center/doctor.
P321	Specific treatment (see on this label).
P363	Wash contaminated clothing before reuse.
P405	Store locked up.
P501	Dispose of contents/container in accordance with local/regional/national/international regulations.

- Hazardous ingredients for labelling

ammonium bifluoride, d-limonene, Alcohols, C9-11 ethoxylated, disodium cocoamphodipropionate

2.3 Other hazards

Special danger of slipping by leaking/spilling product.

Hazards not otherwise classified

Contains d-limonene. May produce an allergic reaction.

Very toxic to aquatic life with long lasting effects (GHS category 1: aquatic toxicity - acute and/or chronic).

Results of PBT and vPvB assessment

Does not contain a PBT-/vPvB-substance at a concentration of $\geq 0.1\%$.

Endocrine disrupting properties

Does not contain an endocrine disruptor (ED) in a concentration of $\geq 0.1\%$.

SECTION 3: Composition/information on ingredients

3.1 Substances

Not relevant (mixture)

3.2 Mixtures

Description of the mixture

Hazardous ingredients acc. to GHS				
Name of substance	Identifier	Wt%	Classification acc. to GHS	Notes
ammonium bifluoride	CAS No 1341-49-7	6 – < 12	Acute Tox. 3 / H301 Skin Corr. 1B / H314	
Alcohols, C9-11 ethoxylated	CAS No 68439-46-3	1 – < 5	Acute Tox. 4 / H302 Acute Tox. 4 / H312 Eye Dam. 1 / H318	

Touchless Wheel Cleaner

Version number: GHS 6.0
Replaces version of: 2024-02-14 (GHS 5)

Revision: 2024-05-17

Hazardous ingredients acc. to GHS				
Name of substance	Identifier	Wt%	Classification acc. to GHS	Notes
polyethoxylated tallow amine	CAS No 61791-26-2	1 – < 5	Acute Tox. 4 / H302 Acute Tox. 4 / H312	
(Amines, N-tallowalkyltri-methylenediamines, ethoxylated	CAS No 61790-85-0	1 – < 5	Acute Tox. 4 / H302	
dipropylene glycol mono-methyl ether	CAS No 34590-94-8	1 – < 2.5	Flam. Liq. 4 / H227	
disodium cocoamphodipropionate	CAS No 68604-71-7	1 – < 1.5	Eye Dam. 1 / H318 Flam. Liq. 4 / H227	
d-limonene	CAS No 5989-27-5	0.1 – < 0.6	Skin Irrit. 2 / H315 Skin Sens. 1 / H317 Flam. Liq. 3 / H226	
methanol	CAS No 67-56-1	0.14 – < 0.19	Acute Tox. 3 / H301 Acute Tox. 3 / H311 Acute Tox. 3 / H331 STOT SE 1 / H370 Flam. Liq. 2 / H225	

Remarks

For full text of abbreviations: see SECTION 16.

This table, if present, includes all GHS classified ingredients present above their cut-off limits, even if the finished product is not classified as hazardous by GHS.

SECTION 4: First-aid measures

4.1 Description of first-aid measures

General notes

Do not leave affected person unattended. Remove victim out of the danger area. Keep affected person warm, still and covered. Take off immediately all contaminated clothing. In all cases of doubt, or when symptoms persist, seek medical advice. In case of unconsciousness place person in the recovery position. Never give anything by mouth.

Following inhalation

If breathing is irregular or stopped, immediately seek medical assistance and start first aid actions. In case of respiratory tract irritation, consult a physician. Provide fresh air.

Following skin contact

Follow water rinsing by massaging with calcium gluconate (2.5%) gel. Continue massaging with gel while seeking medical attention.

Following eye contact

Remove contact lenses, if present and easy to do. Continue rinsing. Irrigate with calcium gluconate (1.0%) solution. Seek immediate medical attention.

Following ingestion

Rinse mouth with water (only if the person is conscious). Do NOT induce vomiting. If patient is conscious and able to swallow give oral calcium solutions or calcium based antacids or milk. Seek immediate medical attention. Consider starting an IV with 10% calcium gluconate.

4.2 Most important symptoms and effects, both acute and delayed

Delayed or immediate effects can be expected after short or long-term exposure. Risk of hypocalcemia (possible life threatening lowering of serum calcium). May cause severe chemical burns which may not be immediately apparent.

Touchless Wheel Cleaner

Version number: GHS 6.0
Replaces version of: 2024-02-14 (GHS 5)

Revision: 2024-05-17

SECTION 5: Fire-fighting measures

5.1 Extinguishing media

Suitable extinguishing media

Water spray, Alcohol resistant foam, BC-powder, Carbon dioxide (CO₂)

5.2 Special hazards arising from the substance or mixture

Hazardous combustion products

Nitrogen oxides (NO_x), Carbon monoxide (CO), Carbon dioxide (CO₂), Hydrogen fluoride (HF)

5.3 Advice for firefighters

In case of fire and/or explosion do not breathe fumes. Coordinate firefighting measures to the fire surroundings. Do not allow firefighting water to enter drains or water courses. Collect contaminated firefighting water separately. Fight fire with normal precautions from a reasonable distance.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

Remove persons to safety.

For emergency responders

Wear breathing apparatus if exposed to vapors/dust/aerosols/gases.

6.2 Environmental precautions

If substance has entered a water course or sewer, inform the responsible authority.

6.3 Methods and material for containment and cleaning up

Advice on how to contain a spill

Covering of drains

Advice on how to clean up a spill

Wipe up with absorbent material (e.g. cloth, fleece). Collect spillage: sawdust, kieselgur (diatomite), sand, universal binder

Appropriate containment techniques

Use of adsorbent materials.

Other information relating to spills and releases

Place in appropriate containers for disposal. Ventilate affected area.

6.4 Reference to other sections

Hazardous combustion products: see section 5. Personal protective equipment: see section 8. Incompatible materials: see section 10. Disposal considerations: see section 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Recommendations

- Measures to prevent fire as well as aerosol and dust generation

Use local and general ventilation. Use only in well-ventilated areas.

Touchless Wheel Cleaner

Version number: GHS 6.0
Replaces version of: 2024-02-14 (GHS 5)

Revision: 2024-05-17

Advice on general occupational hygiene

Wash hands after use. Do not eat, drink and smoke in work areas. Remove contaminated clothing and protective equipment before entering eating areas. Never keep food or drink in the vicinity of chemicals. Never place chemicals in containers that are normally used for food or drink. Keep away from food, drink and animal feedingstuffs.

7.2 Conditions for safe storage, including any incompatibilities

Control of the effects

Protect against external exposure, such as
frost

- Packaging compatibilities

Only packagings which are approved (e.g. acc. to the Dangerous Goods Regulations) may be used.

7.3 Specific end use(s)

See section 16 for a general overview.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limit values (Workplace Exposure Limits)											
Country	Name of agent	CAS No	Identifier	TWA [ppm]	TWA [mg/m ³]	STEL [ppm]	STEL [mg/m ³]	Ceiling-C [ppm]	Ceiling-C [mg/m ³]	Notation	Source
US	(2-methoxy-methylethoxy)propanol	34590-94-8	TLV®	100		150					AC-GIH® 2019
US	dipropylene glycol methyl ether	34590-94-8	PEL (CA)	100	600	150	900			H	Cal/OSHA PEL
US	dipropylene glycol methyl ether	34590-94-8	REL	100 (10 h)	600 (10 h)	150	900			H	NIOSH REL
US	dipropylene glycol methyl ether	34590-94-8	PEL	100	600					H	29 CFR 1910.1000
US	methanol	67-56-1	TLV®	200		250				H	AC-GIH® 2019
US	methyl alcohol	67-56-1	PEL	200	260						29 CFR 1910.1000
US	methyl alcohol	67-56-1	REL	200 (10 h)	260 (10 h)	250	325			H	NIOSH REL
US	methyl alcohol (methanol)	67-56-1	PEL (CA)	200	260	250	325	1,000		H	Cal/OSHA PEL

Notation

Ceiling-C

H

STEL

ceiling value is a limit value above which exposure should not occur absorbed through the skin

short-term exposure limit: a limit value above which exposure should not occur and which is related to a 15-minute period (unless otherwise specified)

Touchless Wheel Cleaner

Version number: GHS 6.0
Replaces version of: 2024-02-14 (GHS 5)

Revision: 2024-05-17

Notation

TWA time-weighted average (long-term exposure limit): measured or calculated in relation to a reference period of 8 hours time-weighted average (unless otherwise specified)

Biological limit values

Country	Name of agent	Parameter	Notation	Identifier	Value	Source
US	methanol	methanol		BEI®	15 mg/l	ACGIH® 2019

Relevant DNELs of components

Name of substance	CAS No	End-point	Threshold level	Protection goal, route of exposure	Used in	Exposure time
ammonium bifluoride	1341-49-7	DNEL	2.3 mg/m³	human, inhalatory	worker (industry)	chronic - systemic effects
ammonium bifluoride	1341-49-7	DNEL	3.8 mg/m³	human, inhalatory	worker (industry)	acute - local effects
dipropylene glycol monomethyl ether	34590-94-8	DNEL	950 mg/kg	human, dermal	worker (industry)	chronic - systemic effects
dipropylene glycol monomethyl ether	34590-94-8	DNEL	404 mg/m³	human, inhalatory	worker (industry)	chronic - systemic effects
Alcohols, C9-11 ethoxylated	68439-46-3	DNEL	2,080 mg/kg	human, dermal	worker (industry)	chronic - systemic effects
Alcohols, C9-11 ethoxylated	68439-46-3	DNEL	294 mg/m³	human, inhalatory	worker (industry)	chronic - systemic effects
d-limonene	5989-27-5	DNEL	67 mg/m³	human, inhalatory	worker (industry)	chronic - systemic effects
d-limonene	5989-27-5	DNEL	9.5 mg/kg bw/day	human, dermal	worker (industry)	chronic - systemic effects
methanol	67-56-1	DNEL	130 mg/m³	human, inhalatory	worker (industry)	chronic - systemic effects
methanol	67-56-1	DNEL	130 mg/m³	human, inhalatory	worker (industry)	acute - systemic effects
methanol	67-56-1	DNEL	130 mg/m³	human, inhalatory	worker (industry)	chronic - local effects
methanol	67-56-1	DNEL	130 mg/m³	human, inhalatory	worker (industry)	acute - local effects
methanol	67-56-1	DNEL	20 mg/kg bw/day	human, dermal	worker (industry)	chronic - systemic effects
methanol	67-56-1	DNEL	20 mg/kg bw/day	human, dermal	worker (industry)	acute - systemic effects

Touchless Wheel Cleaner

Version number: GHS 6.0
Replaces version of: 2024-02-14 (GHS 5)

Revision: 2024-05-17

Relevant PNECs of components						
Name of substance	CAS No	End-point	Threshold level	Organism	Environmental compartment	Exposure time
ammonium bifluoride	1341-49-7	PNEC	76 mg/l	microorganisms	sewage treatment plant (STP)	short-term (single instance)
ammonium bifluoride	1341-49-7	PNEC	1.3 mg/l	aquatic organisms	freshwater	short-term (single instance)
ammonium bifluoride	1341-49-7	PNEC	76 mg/l	aquatic organisms	sewage treatment plant (STP)	short-term (single instance)
ammonium bifluoride	1341-49-7	PNEC	22 mg/kg	terrestrial organisms	soil	short-term (single instance)
dipropylene glycol monomethyl ether	34590-94-8	PNEC	4,168 mg/l	microorganisms	sewage treatment plant (STP)	short-term (single instance)
dipropylene glycol monomethyl ether	34590-94-8	PNEC	19 mg/l	aquatic organisms	freshwater	short-term (single instance)
dipropylene glycol monomethyl ether	34590-94-8	PNEC	1.9 mg/l	aquatic organisms	marine water	short-term (single instance)
dipropylene glycol monomethyl ether	34590-94-8	PNEC	4,168 mg/l	aquatic organisms	sewage treatment plant (STP)	short-term (single instance)
dipropylene glycol monomethyl ether	34590-94-8	PNEC	2.2 mg/kg	terrestrial organisms	soil	short-term (single instance)
dipropylene glycol monomethyl ether	34590-94-8	PNEC	192 mg/l	aquatic organisms	water	intermittent release
Alcohols, C9-11 ethoxylated	68439-46-3	PNEC	0.1 mg/l	aquatic organisms	freshwater	short-term (single instance)
Alcohols, C9-11 ethoxylated	68439-46-3	PNEC	0.1 mg/l	aquatic organisms	marine water	short-term (single instance)
Alcohols, C9-11 ethoxylated	68439-46-3	PNEC	1.4 mg/l	microorganisms	sewage treatment plant (STP)	short-term (single instance)
Alcohols, C9-11 ethoxylated	68439-46-3	PNEC	14 mg/kg	benthic organisms	sediment	short-term (single instance)
Alcohols, C9-11 ethoxylated	68439-46-3	PNEC	14 mg/kg	pelagic organisms	sediment	short-term (single instance)
Alcohols, C9-11 ethoxylated	68439-46-3	PNEC	1 mg/kg	terrestrial organisms	soil	short-term (single instance)
Alcohols, C9-11 ethoxylated	68439-46-3	PNEC	0.014 mg/l	aquatic organisms	water	intermittent release
d-limonene	5989-27-5	PNEC	1.8 mg/l	microorganisms	sewage treatment plant (STP)	short-term (single instance)
d-limonene	5989-27-5	PNEC	1.3 mg/kg	benthic organisms	sediment	short-term (single instance)
d-limonene	5989-27-5	PNEC	0.13 mg/kg	pelagic organisms	sediment	short-term (single instance)
d-limonene	5989-27-5	PNEC	3.3 mg/kg	(top) predators	water	short-term (single instance)
d-limonene	5989-27-5	PNEC	14 µg/l	aquatic organisms	freshwater	short-term (single instance)

Touchless Wheel Cleaner

Version number: GHS 6.0
Replaces version of: 2024-02-14 (GHS 5)

Revision: 2024-05-17

Relevant PNECs of components						
Name of substance	CAS No	End-point	Threshold level	Organism	Environmental compartment	Exposure time
d-limonene	5989-27-5	PNEC	1.4 µg/l	aquatic organisms	marine water	short-term (single instance)
d-limonene	5989-27-5	PNEC	1.8 mg/l	aquatic organisms	sewage treatment plant (STP)	short-term (single instance)
d-limonene	5989-27-5	PNEC	3.9 mg/kg	aquatic organisms	freshwater sediment	short-term (single instance)
d-limonene	5989-27-5	PNEC	0.39 mg/kg	aquatic organisms	marine sediment	short-term (single instance)
d-limonene	5989-27-5	PNEC	0.76 mg/kg	terrestrial organisms	soil	short-term (single instance)
methanol	67-56-1	PNEC	100 mg/l	microorganisms	sewage treatment plant (STP)	short-term (single instance)
methanol	67-56-1	PNEC	77 mg/kg	benthic organisms	sediment	short-term (single instance)
methanol	67-56-1	PNEC	7.7 mg/kg	pelagic organisms	sediment	short-term (single instance)
methanol	67-56-1	PNEC	1,540 mg/l	aquatic organisms	water	intermittent release
methanol	67-56-1	PNEC	21 mg/l	aquatic organisms	freshwater	short-term (single instance)
methanol	67-56-1	PNEC	2.1 mg/l	aquatic organisms	marine water	short-term (single instance)
methanol	67-56-1	PNEC	100 mg/l	aquatic organisms	sewage treatment plant (STP)	short-term (single instance)
methanol	67-56-1	PNEC	77 mg/kg	aquatic organisms	freshwater sediment	short-term (single instance)
methanol	67-56-1	PNEC	7.7 mg/kg	aquatic organisms	marine sediment	short-term (single instance)
methanol	67-56-1	PNEC	100 mg/kg	terrestrial organisms	soil	short-term (single instance)

8.2 Exposure controls

Appropriate engineering controls

General ventilation.

Individual protection measures (personal protective equipment)

Eye/face protection

Wear eye/face protection.

Skin protection

- Hand protection

Wear suitable gloves. Chemical protection gloves are suitable, which are tested according to EN 374. Check leak-tightness/impermeability prior to use. In the case of wanting to use the gloves again, clean them before taking off and air them well. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

Touchless Wheel Cleaner

Version number: GHS 6.0
Replaces version of: 2024-02-14 (GHS 5)

Revision: 2024-05-17

- Other protection measures

Take recovery periods for skin regeneration. Preventive skin protection (barrier creams/ointments) is recommended. Wash hands thoroughly after handling.

Environmental exposure controls

Use appropriate container to avoid environmental contamination. Keep away from drains, surface and ground water.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance

Physical state	liquid (viscous)
Color	translucent - colorless to pale amber
Particle	not relevant (liquid)
Odor	characteristic

Other safety parameters

pH (value)	3 – 5 (25 °C)
Melting point/freezing point	not determined
Initial boiling point and boiling range	90 °C
Flash point	>100 °C at 101 kPa
Evaporation rate	Not determined
Flammability (solid, gas)	not relevant, (fluid)

Explosive limits

- Lower explosion limit (LEL)	1.1 vol%
- Upper explosion limit (UEL)	3 vol%
Vapor pressure	32 hPa at 25 °C
Density	1 g/ml
Vapor density	this information is not available

Solubility(ies)

- Water solubility	miscible in any proportion
--------------------	----------------------------

Partition coefficient

- n-octanol/water (log KOW)	this information is not available
-----------------------------	-----------------------------------

Touchless Wheel Cleaner

Version number: GHS 6.0
Replaces version of: 2024-02-14 (GHS 5)

Revision: 2024-05-17

Auto-ignition temperature	>150 °C
Viscosity	not determined
Explosive properties	none
Oxidizing properties	none

9.2 Other information

Temperature class (USA, acc. to NEC 500)	T4 (maximum permissible surface temperature on the equipment: 135 °C)
--	---

SECTION 10: Stability and reactivity

10.1 Reactivity

Concerning incompatibility: see below "Conditions to avoid" and "Incompatible materials".

10.2 Chemical stability

See below "Conditions to avoid".

10.3 Possibility of hazardous reactions

No known hazardous reactions.

10.4 Conditions to avoid

There are no specific conditions known which have to be avoided.

10.5 Incompatible materials

Oxidizers

10.6 Hazardous decomposition products

Reasonably anticipated hazardous decomposition products produced as a result of use, storage, spill and heating are not known. Hazardous combustion products: see section 5.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Test data are not available for the complete mixture.

Classification procedure

The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

Classification acc. to OSHA "Hazard Communication Standard" (29 CFR 1910.1200)

Acute toxicity

Harmful if swallowed.

- Acute toxicity estimate (ATE)

Oral >1,034 mg/kg

Touchless Wheel Cleaner

Version number: GHS 6.0
Replaces version of: 2024-02-14 (GHS 5)

Revision: 2024-05-17

Acute toxicity estimate (ATE) of components			
Name of substance	CAS No	Exposure route	ATE
ammonium bifluoride	1341-49-7	oral	130 mg/kg
Alcohols, C9-11 ethoxylated	68439-46-3	oral	1,200 mg/kg
Alcohols, C9-11 ethoxylated	68439-46-3	dermal	2,000 mg/kg
polyethoxylated tallow amine	61791-26-2	oral	1,437 mg/kg
polyethoxylated tallow amine	61791-26-2	dermal	>1,260 mg/kg
(Amines, N-tallowalkyltrimethylenediamines, ethoxylated	61790-85-0	oral	>500 mg/kg
methanol	67-56-1	oral	100 mg/kg
methanol	67-56-1	inhalation: gas	700 ppmV/4h
methanol	67-56-1	inhalation: dust/mist	0.5 mg/l/4h

Skin corrosion/irritation

Causes severe skin burns and eye damage.

Serious eye damage/eye irritation

Causes serious eye damage.

Respiratory or skin sensitization

May cause an allergic skin reaction.

Germ cell mutagenicity

Shall not be classified as germ cell mutagenic.

Carcinogenicity

Shall not be classified as carcinogenic.

IARC Monographs on the Evaluation of Carcinogenic Risks to Humans				
Name of substance	CAS No	Classification	Remarks	Number
d-limonene	5989-27-5	3		

Legend

3 Not classifiable as to carcinogenicity in humans

Reproductive toxicity

Shall not be classified as a reproductive toxicant.

Specific target organ toxicity - single exposure

Shall not be classified as a specific target organ toxicant (single exposure).

Specific target organ toxicity - repeated exposure

Shall not be classified as a specific target organ toxicant (repeated exposure).

Aspiration hazard

Shall not be classified as presenting an aspiration hazard.

Touchless Wheel Cleaner

Version number: GHS 6.0
Replaces version of: 2024-02-14 (GHS 5)

Revision: 2024-05-17

SECTION 12: Ecological information

12.1 Toxicity

Very toxic to aquatic life with long lasting effects.

Aquatic toxicity (acute) of components					
Name of substance	CAS No	Endpoint	Value	Species	Exposure time
ammonium bifluoride	1341-49-7	LC50	421 mg/l	fish	96 h
dipropylene glycol monomethyl ether	34590-94-8	LC50	>150 mg/l	fish	72 h
dipropylene glycol monomethyl ether	34590-94-8	ErC50	>969 mg/l	algae	72 h
Alcohols, C9-11 ethoxylated	68439-46-3	LC50	8.5 mg/l	fathead minnow	96 h
Alcohols, C9-11 ethoxylated	68439-46-3	EC50	5.3 mg/l	daphnia magna	48 h
Alcohols, C9-11 ethoxylated	68439-46-3	ErC50	1 – 10 mg/l	algae	96 h
polyethoxylated tallow amine	61791-26-2	LC50	0.19 mg/l	fish	96 h
polyethoxylated tallow amine	61791-26-2	LC50	0.99 mg/l	fish	96 h
polyethoxylated tallow amine	61791-26-2	EC50	0.008 mg/l	algae	48 h
polyethoxylated tallow amine	61791-26-2	EC50	0.47 mg/l	daphnia	48 h
disodium cocoamphodipropionate	68604-71-7	LC50	1 – 100 mg/l	fish	72 h
disodium cocoamphodipropionate	68604-71-7	EC50	0.55 – 48 mg/l	algae	72 h
disodium cocoamphodipropionate	68604-71-7	EC50	6.5 mg/l	daphnia	48 h
(Amines, N-tallowalkyltrimethylenediamines, ethoxylated)	61790-85-0	LC50	0.1 mg/l	fish	96 h
(Amines, N-tallowalkyltrimethylenediamines, ethoxylated)	61790-85-0	LC50	0.15 mg/l	fish	96 h
d-limonene	5989-27-5	LC50	720 µg/l	fish	96 h
d-limonene	5989-27-5	EC50	688 µg/l	fish	96 h
d-limonene	5989-27-5	ErC50	0.32 mg/l	algae	72 h
methanol	67-56-1	LC50	15,400 mg/l	fish	96 h
methanol	67-56-1	EC50	12,700 mg/l	fish	96 h
methanol	67-56-1	ErC50	22,000 mg/l	algae	96 h

Touchless Wheel Cleaner

Version number: GHS 6.0
Replaces version of: 2024-02-14 (GHS 5)

Revision: 2024-05-17

Aquatic toxicity (chronic) of components					
Name of substance	CAS No	Endpoint	Value	Species	Exposure time
d-limonene	5989-27-5	EC50	<0.67 mg/l	fish	8 d
d-limonene	5989-27-5	LC50	0.41 mg/l	fish	8 d

12.2 Persistence and degradability

Data are not available.

12.3 Bioaccumulative potential

Data are not available.

12.4 Mobility in soil

Data are not available.

12.5 Results of PBT and vPvB assessment

According to the results of its assessment, this substance is not a PBT or a vPvB. Does not contain a PBT-/vPvB-substance at a concentration of $\geq 0.1\%$.

12.6 Endocrine disrupting properties

Does not contain an endocrine disruptor (ED) in a concentration of $\geq 0.1\%$.

12.7 Other adverse effects

Data are not available.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Sewage disposal-relevant information

Do not empty into drains. Avoid release to the environment. Refer to special instructions/safety data sheets.

Waste treatment of containers/packages

Only packagings which are approved (e.g. acc. to DOT) may be used. Completely emptied packages can be recycled. Handle contaminated packages in the same way as the substance itself.

Remarks

Please consider the relevant national or regional provisions. Waste shall be separated into the categories that can be handled separately by the local or national waste management facilities.

SECTION 14: Transport information

14.1 UN number

DOT	UN 2922
IMDG-Code	UN 2922
ICAO-TI	UN 2922

14.2 UN proper shipping name

DOT	Corrosive liquid, toxic, n.o.s.
IMDG-Code	CORROSIVE LIQUID, TOXIC, N.O.S.
ICAO-TI	Corrosive liquid, toxic, n.o.s.

Touchless Wheel Cleaner

Version number: GHS 6.0
Replaces version of: 2024-02-14 (GHS 5)

Revision: 2024-05-17

Technical name (hazardous ingredients)	ammonium bifluoride, methanol
14.3 Transport hazard class(es)	
DOT	8 (6.1)
IMDG-Code	8 (6.1)
ICAO-TI	8 (6.1)
14.4 Packing group	
DOT	II
IMDG-Code	II
ICAO-TI	II
14.5 Environmental hazards	hazardous to the aquatic environment
Environmentally hazardous substance (aquatic environment)	polyethoxylated tallow amine
14.6 Special precautions for user	
There is no additional information.	
14.7 Transport in bulk according to IMO instruments	
The cargo is not intended to be carried in bulk.	

Information for each of the UN Model Regulations

Transport of dangerous goods by road or rail (49 CFR US DOT)

Particulars in the shipper's declaration	UN2922, Corrosive liquid, toxic, n.o.s., (contains: ammonium bifluoride, methanol), 8 (6.1), II, environmentally hazardous
Reportable quantity (RQ)	865 lbs (393 kg) (ammonium bifluoride) (methanol)
Danger label(s)	8+6.1, fish and tree
	
Environmental hazards	yes (hazardous to the aquatic environment)
Special provisions (SP)	B3, IB2, T7, TP2
ERG No	154

International Maritime Dangerous Goods Code (IMDG)

Marine pollutant	yes (hazardous to the aquatic environment) (polyethoxylated tallow amine)
Danger label(s)	8+6.1, fish and tree
	
Special provisions (SP)	274
Excepted quantities (EQ)	E2
Limited quantities (LQ)	1 L
EmS	F-A, S-B
Stowage category	B

Touchless Wheel Cleaner

Version number: GHS 6.0
Replaces version of: 2024-02-14 (GHS 5)

Revision: 2024-05-17

International Civil Aviation Organization (ICAO-IATA/DGR)

Environmental hazards yes (hazardous to the aquatic environment)

Danger label(s) 8+6.1



Special provisions (SP) A3

Excepted quantities (EQ) E2

Limited quantities (LQ) 0,5 L

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations specific for the product in question

National regulations (United States)

Toxic Substance Control Act (TSCA) all ingredients are listed

Superfund Amendment and Reauthorization Act (SARA TITLE III)

- The List of Extremely Hazardous Substances and Their Threshold Planning Quantities (EPCRA Section 302, 304)

none of the ingredients are listed

- Specific Toxic Chemical Listings (EPCRA Section 313)

Toxics Release Inventory: Specific Toxic Chemical Listings			
Name of substance	CAS No	Remarks	Effective date
methanol	67-56-1		1986-12-31

Comprehensive Environmental Response, Compensation, and Liability Act (CERCLA)

- List of Hazardous Substances and Reportable Quantities (CERCLA section 102a) (40 CFR 302.4)

Name of substance	CAS No	Remarks	Statutory code	Final RQ pounds (Kg)
methanol	67-56-1		3 4	5000 (2270)
ammonium bifluoride	1341-49-7		1	100 (45,4)

Legend

- 1 "1" indicates that the statutory source is section 311(b)(2) of the Clean Water Act
3 "3" indicates that the source is section 112 of the Clean Air Act
4 "4" indicates that the source is section 3001 of the Resource Conservation and Recovery Act (RCRA)

Clean Air Act

none of the ingredients are listed

Right to Know Hazardous Substance List

Touchless Wheel Cleaner

Version number: GHS 6.0
Replaces version of: 2024-02-14 (GHS 5)

Revision: 2024-05-17

- Cleaning Product Right to Know Act Substance List (CA-RTK)

Name of substance	CAS No	Functionality	Authoritative Lists
water	7732-18-5	solvent	
ammonium bifluoride	1341-49-7	metal cleaner	
dipropylene glycol monomethyl ether	34590-94-8	surfactant	
Alcohols, C9-11 ethoxylated	68439-46-3	surfactant	
polyethoxylated tallow amine	61791-26-2	surfactant	
disodium cocoamphodipropionate	68604-71-7	surfactant	
(Amines, N-tallowalkyltrimethylenediamines, ethoxylated)	61790-85-0	surfactant	
d-limonene	5989-27-5		EU Fragrance Allergens
methanol	67-56-1	alcohols	CA TACs NTP OHAT - Repr. or Dev. Toxicants OEHA RELs Prop 65
cocoyl hydroxyethylimidazoline	61791-38-6	non-functional constituent	

- Toxic or Hazardous Substance List (MA-TURA)

Name of substance	CAS No	DEP CODE	PBT / HHS / LHS	PBT / HHS Threshold	De Minimis Concentration Threshold
methanol	67-56-1				1.0 %
ammonium bifluoride	1341-49-7				1.0 %
ammonium bifluoride	7664-41-7				1.0 %

- Hazardous Substances List (MN-ERTK)

Name of substance	CAS No	References	Remarks
dipropylene glycol monomethyl ether	34590-94-8	A, O	

Legend

- A American Conference of Governmental Industrial Hygienists (ACGIH), "Threshold Limit Values for Chemical Substances and Physical Agents and Biological Exposure Indices for 1992-93", available from ACGIH
- O Occupational Safety and Health Administration (OSHA), Safety and Health Standards, Code of Federal Regulations, title 29, part 1910, subpart Z, "Toxic and Hazardous Substances, 1990." General information: Minnesota Department of Labor and Industry, Occupational Safety and Health Division

- Hazardous Substance List (NJ-RTK)

Name of substance	CAS No	Remarks	Classifications
methanol	67-56-1		TE F3
ammonium bifluoride	1341-49-7		CO
dipropylene glycol monomethyl ether	34590-94-8		F2
d-limonene	138-86-3		F2

Touchless Wheel Cleaner

Version number: GHS 6.0
Replaces version of: 2024-02-14 (GHS 5)

Revision: 2024-05-17

Legend

CO	Corrosive
F2	Flammable - Second Degree
F3	Flammable - Third Degree
TE	Teratogenic

- Hazardous Substance List (Chapter 323) (PA-RTK)

Name acc. to inventory	CAS No	Classification
METHANOL	67-56-1	E
AMMONIUM FLUORIDE ((NH ₄)(HF ₂))	1341-49-7	E
PROPANOL, (2-METHOXYMETHYLETH-OXY)-	34590-94-8	

Legend

E	Environmental hazard
---	----------------------

- Hazardous Substance List (RI-RTK)

Name of substance	CAS No	References
methanol	67-56-1	T, F
dipropylene glycol monomethyl ether	34590-94-8	T

Legend

F	Flammability (NFPA®)
T	Toxicity (ACGIH®)

California Environmental Protection Agency (Cal/EPA): Proposition 65 - Safe Drinking Water and Toxic Enforcement Act of 1987

Proposition 65 List of chemicals				
Name acc. to inventory	CAS No	Conc.	Remarks	Type of the toxicity
methanol	67-56-1	0.17 wt%		developmental

VOC content

- Regulated Volatile Organic Compounds (VOC-EPA)	3.1 %
- Regulated Volatile Organic Compounds (VOC-Cal ARB)	3.1 %

Industry or sector specific available guidance(s)

NPCA-HMIS® III

Hazardous Materials Identification System. American Coatings Association.

Category	Rating	Description
Chronic	/	none
Health	3	major injury likely unless prompt action is taken and medical treatment is given
Flammability	1	material that must be preheated before ignition can occur
Physical hazard	0	material that is normally stable, even under fire conditions, and will not react with water, polymerize, decompose, condense, or self-react. Non-explosive

Touchless Wheel Cleaner

Version number: GHS 6.0
Replaces version of: 2024-02-14 (GHS 5)

Revision: 2024-05-17

Category	Rating	Description
Personal protection	-	
Chronic:	chronic hazard	
Flammability:	flammability hazards	
Health:	health hazard	
Personal protection:	personal protective equipment (PPE) for normal use	
Physical hazard:	reactivity	

NFPA® 704

National Fire Protection Association: Standard System for the Identification of the Hazards of Materials for Emergency Response (United States).

Category	Degree of hazard	Description
Flammability	1	material that must be preheated before ignition can occur
Health	3	material that, under emergency conditions, can cause serious or permanent injury
Instability	0	material that is normally stable, even under fire conditions
Special hazard		

National inventories

Country	Inventory	Status
CA	DSL	all ingredients are listed
EU	REACH Reg.	not all ingredients are listed
US	TSCA	all ingredients are listed (ACTIVE)
AU	AIIC	all ingredients are listed
CN	IECSC	all ingredients are listed
EU	ECSI	not all ingredients are listed
JP	CSCL-ENCS	not all ingredients are listed
JP	ISHA-ENCS	not all ingredients are listed
KR	KECI	all ingredients are listed
MX	INSQ	not all ingredients are listed
NZ	NZIoC	all ingredients are listed
PH	PICCS	all ingredients are listed
TR	CICR	not all ingredients are listed
TW	TCSI	all ingredients are listed
VN	NCI	all ingredients are listed

Legend

AIIC	Australian Inventory of Industrial Chemicals
CICR	Chemical Inventory and Control Regulation
CSCL-ENCS	List of Existing and New Chemical Substances (CSCL-ENCS)
DSL	Domestic Substances List (DSL)
ECSI	EC Substance Inventory (EINECS, ELINCS, NLP)
IECSC	Inventory of Existing Chemical Substances Produced or Imported in China
INSQ	National Inventory of Chemical Substances
ISHA-ENCS	Inventory of Existing and New Chemical Substances (ISHA-ENCS)
KECI	Korea Existing Chemicals Inventory

Touchless Wheel Cleaner

Version number: GHS 6.0
Replaces version of: 2024-02-14 (GHS 5)

Revision: 2024-05-17

Legend

NCI	National Chemical Inventory
NZIoC	New Zealand Inventory of Chemicals
PICCS	Philippine Inventory of Chemicals and Chemical Substances (PICCS)
REACH Reg.	REACH registered substances
TCSI	Taiwan Chemical Substance Inventory
TSCA	Toxic Substance Control Act

Additional information

The contained substances are listed in the following national inventories:

AICS (Australia)
DSL/NDSL (Canada)
IECSC (China)
KECL (Republic of Korea)
NZIoC (New Zealand)
PICCS (Philippines)
TCSI (Taiwan)
TSCA (United States)

15.2 Chemical Safety Assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information, including date of preparation or last revision

Indication of changes (revised safety data sheet)

Alignment to regulation: Globally Harmonized System of Classification and Labelling of Chemicals ("Purple book").
Restructuring: section 9, section 14

Section	Former entry (text/value)	Actual entry (text/value)	Safety-relevant
4.1	Following ingestion: Rinse mouth with water (only if the person is conscious). Do NOT induce vomiting. If patient is conscious and able to swallow give oral calcium solutions or calcium based antacids or milk. Seek immediate medical attention.	Following ingestion: Rinse mouth with water (only if the person is conscious). Do NOT induce vomiting. If patient is conscious and able to swallow give oral calcium solutions or calcium based antacids or milk. Seek immediate medical attention. Consider starting an IV with 10% calcium gluconate.	yes
8.1		Occupational exposure limit values (Workplace Exposure Limits): change in the listing (table)	yes
15.1		Additional information: The contained substances are listed in the following national inventories: AICS (Australia) DSL/NDSL (Canada) IECSC (China) KECL (Republic of Korea) NZIoC (New Zealand) PICCS (Philippines) TCSI (Taiwan) TSCA (United States)	yes

Abbreviations and acronyms

Touchless Wheel Cleaner

Version number: GHS 6.0
Replaces version of: 2024-02-14 (GHS 5)

Revision: 2024-05-17

Abbr.	Descriptions of used abbreviations
29 CFR 1910.1000	29 CFR 1910.1000, Tables Z-1, Z-2, Z-3 - Occupational Safety and Health Standards: Toxic and Hazardous Substances (permissible exposure limits)
49 CFR US DOT	49 CFR U.S. Department of Transportation
ACGIH®	American Conference of Governmental Industrial Hygienists
ACGIH® 2019	From ACGIH®, 2019 TLVs® and BEIs® Book. Copyright 2019. Reprinted with permission. Information on the proper use of the TLVs® and BEIs®: http://www.acgih.org/tlv-bei-guidelines/policies-procedures-presentations/tlv-bei-position-statement
Acute Tox.	Acute toxicity
ATE	Acute Toxicity Estimate
Cal/OSHA PEL	California Division of Occupational Safety and Health (Cal/OSHA): Permissible Exposure Limits (PELs)
Cal ARB	California Air Resources Board
CAS	Chemical Abstracts Service (service that maintains the most comprehensive list of chemical substances)
Ceiling-C	Ceiling value
DEP CODE	Department of Environmental Protection Code
DGR	Dangerous Goods Regulations (see IATA/DGR)
DNEL	Derived No-Effect Level
DOT	Department of Transportation (USA)
EC50	Effective Concentration 50 %. The EC50 corresponds to the concentration of a tested substance causing 50 % changes in response (e.g. on growth) during a specified time interval
ED	Endocrine disruptor
EINECS	European Inventory of Existing Commercial Chemical Substances
ELINCS	European List of Notified Chemical Substances
EmS	Emergency Schedule
EPA	Environmental Protection Agency. An agency of the federal government of the United States charged with protecting human health and the environment
ErC50	≡ EC50: in this method, that concentration of test substance which results in a 50 % reduction in either growth (EbC50) or growth rate (ErC50) relative to the control
ERG No	Emergency Response Guidebook - Number
Eye Dam.	Seriously damaging to the eye
Eye Irrit.	Irritant to the eye
Flam. Liq.	Flammable liquid
GHS	"Globally Harmonized System of Classification and Labelling of Chemicals" developed by the United Nations
HHS	Higher hazard substance
IARC	International Agency for Research on Cancer
IATA	International Air Transport Association
IATA/DGR	Dangerous Goods Regulations (DGR) for the air transport (IATA)
ICAO	International Civil Aviation Organization
ICAO-TI	Technical instructions for the safe transport of dangerous goods by air

Touchless Wheel Cleaner

Version number: GHS 6.0
Replaces version of: 2024-02-14 (GHS 5)

Revision: 2024-05-17

Abbr.	Descriptions of used abbreviations
IMDG	International Maritime Dangerous Goods Code
IMDG-Code	International Maritime Dangerous Goods Code
LC50	Lethal Concentration 50%: the LC50 corresponds to the concentration of a tested substance causing 50 % lethality during a specified time interval
LHS	Lower hazard substance
NFPA®	National Fire Protection Association (United States)
NIOSH REL	National Institute for Occupational Safety and Health (NIOSH): Recommended Exposure Limits (RELs)
NLP	No-Longer Polymer
NPCA-HMIS® III	National Paint and Coatings Association: Hazardous Materials Identification System - HMIS® III, Third Edition
OSHA	Occupational Safety and Health Administration (United States)
PBT	Persistent, Bioaccumulative and Toxic
PEL	Permissible exposure limit
PNEC	Predicted No-Effect Concentration
ppm	Parts per million
Skin Corr.	Corrosive to skin
Skin Irrit.	Irritant to skin
Skin Sens.	Skin sensitization
STEL	Short-term exposure limit
STOT SE	Specific target organ toxicity - single exposure
TLV®	Threshold Limit Values
TWA	Time-weighted average
VOC	Volatile Organic Compounds
vPvB	Very Persistent and very Bioaccumulative

Key literature references and sources for data

OSHA Hazard Communication Standard (HCS), 29 CFR 1910.1200.

Transport of dangerous goods by road or rail (49 CFR US DOT). International Maritime Dangerous Goods Code (IMDG). Dangerous Goods Regulations (DGR) for the air transport (IATA).

Classification procedure

Physical and chemical properties: The classification is based on tested mixture.

Health hazards, Environmental hazards: The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

List of relevant phrases (code and full text as stated in section 2 and 3)

Touchless Wheel Cleaner

Version number: GHS 6.0
Replaces version of: 2024-02-14 (GHS 5)

Revision: 2024-05-17

Code	Text
H225	Highly flammable liquid and vapor.
H226	Flammable liquid and vapor.
H227	Combustible liquid.
H301	Toxic if swallowed.
H302	Harmful if swallowed.
H311	Toxic in contact with skin.
H312	Harmful in contact with skin.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H331	Toxic if inhaled.
H370	Causes damage to organs.

Disclaimer

This information is based upon the present state of our knowledge. This SDS has been compiled and is solely intended for this product.