

• TRUSTED QUALITY SINCE 1921 •

**RUST-OLEUM®****PENETRATING CONCRETE SEALER****DESCRIPTION AND USES**

Rust-Oleum® Penetrating Concrete Sealer seals and protects bare concrete and masonry surfaces (including landscaping blocks and concrete pavers) from the damaging effects of water, chemicals and UV light without changing the appearance of the concrete. This water-base formula penetrates deeply into and reacts with the concrete to form a protective barrier beneath the surface to keep water out, protect against stains and extend the life of the concrete surface.

It is suitable for use on interior or exterior, bare concrete and masonry surfaces. Do not use on asphalt. It is ideal for driveways, walkways, porches, pool decks, basements and more.

This product is not for use on previously painted or stained floors or over loose or poorly cured concrete. Areas subject to hydrostatic pressure are best coated with a waterproofing paint. Not recommended for use on garage floors where a film forming sealer is present.

**PRODUCTS**

SKU	Container Size
310429	1-Gallon Penetrating Concrete Sealer

**PRODUCT FEATURES**

- Penetrates concrete for chemical & stain protection
- Excellent water repellency
- Maintains original appearance

**PRODUCT APPLICATION****READ ALL INSTRUCTIONS CAREFULLY BEFORE STARTING PROJECT****SURFACE PREPARATION**

Proper surface preparation is critical to achieve best results. Allow newly poured concrete to cure for a minimum of 28 days. Sweep away all loose dirt, debris and remove any vegetation that could interfere with application and performance. If necessary, use a wire brush or sander to remove any loose or unsound concrete or masonry. Remove any efflorescence with an efflorescence remover (sold separately). Clean the entire surface, including any oil or grease spots with Rust-Oleum Cleaner & Degreaser (sold separately). Scrub the surface with a stiff bristle brush or broom. Rinse thoroughly with fresh water, preferably with a power washer. Repeat as necessary to completely clean and rinse. Allow to dry to the touch (typically 4-6 hours) before applying product.

**PRODUCT APPLICATION (cont.)****APPLICATION**

Rust-Oleum Penetrating Concrete Sealer is ready to use. Do not thin. Use only when air (ambient) temperature is between 50-90°F (10-32°C) and the relative humidity is below 85% during the day and night. **Do not apply in direct sunlight.** Do not apply if rain is expected within 24 hours. Use in a well ventilated area. Avoid applying late in the day when temperatures are falling as the formation of dew can interfere with proper sealing.

Mask adjacent surfaces to allow spray application up to all edges. Protect delicate foliage from overspray. Apply using a standard pump sprayer with an adjustable spray tip or apply using a standard 3/8" nap roller. Choose the best applicator for the size of the project and texture of the concrete. Do not pour the sealer directly on the surface or allow to puddle.

Stir the container to mix product. Fill pump sprayer with product, then fully pressurize the sprayer. Set the spray tip to a medium-fine mist and spray 10-12" from the surface. Start and stop the sprayer just off the work area to prevent drips. For larger areas, work in 6'x6' sections at a time before moving to the next section. Apply the product evenly, using a circular or oval pattern to saturate the surface. Do not allow the sealer to puddle. Back roll any puddles using a 3/8" nap roller.

**Once sealed, it is no longer a paintable surface.** For ongoing maintenance, surfaces previously sealed with Rust-Oleum Penetrating Concrete Sealer (or another water-based penetrating concrete sealer) may be sealed again with this product.

**COVERAGE**

Each gallon covers approximately 250 square feet (single coat). Coverage will vary depending on the porosity of the surface. Porous surfaces may require multiple coats.

**DRY TIME**

Dry time is based on 70°F and 50% relative humidity. Allow longer dry time at lower temperatures and higher humidity. Wait a minimum of 4-6 hours for light foot traffic. Wait 24-48 hours before returning heavy items, furniture and vehicles. The surface will be fully cured in 72 hours.

**CLEAN-UP**

Soap and water. Properly dispose of all soiled rags, roller covers and unused product.

## TECHNICAL DATA

# PENETRATING CONCRETE SEALER

### PHYSICAL PROPERTIES

Resin Type		Silane and Siloxane Materials
Pigment		None
Solvent		Water
Weight	Per Gallon	8.3 lbs.
	Per Liter	1.00 kg
Solids	By Weight	5.0%
	By Volume	5.5%
Volatile Organic Compounds		<10 g/l (0.08 lbs./gal.)
Practical Coverage at Recommended DFT		250 sq.ft./gal. (single coat) Actual coverage will vary depending on the porosity of the surface
Dry Times @ 70-80° F (21-27°C) and 50% Relative Humidity	Light Foot Traffic	4-6 hours
	Return Furniture	24-48 hours
	Full Cure	72 hours
Shelf Life		2 years
Flash Point		>200°F (93°C)
Safety Information		For additional information, see SDS

The technical data and suggestions for use contained herein are correct to the best of our knowledge, and offered in good faith. The statements of this literature do not constitute a warranty, express, or implied, as to the performance of these products. As conditions and use of our materials are beyond our control, we can guarantee these products only to conform to our standards of quality, and our liability, if any, will be limited to replacement of defective materials. All technical information is subject to change without notice.